







## 9 Reasons to Choose Century Prowud ARTZ Embossed Panels

- 1. Century Prowud ARTZ panels are ideally suited for polishing, painting, membrane pressing and many other applications.
- 2. Century Prowud ARTZ is made with the latest available technology using the best quality plates, which gives sharp edges to the embossed design and a glossy-smooth finish to the surface.
- 3. Century Prowud ARTZ has a wide range of aesthetically superior designs.
- 4. Uniform and high density, and online quality control systems make this product consistent and superior than other available products in the market.
- 5. Uniform and high-internal bonding in panels is used for embossing that gives the best quality and performance during application.
- 6. High density of ARTZ Embossed Panels minimises permeability and paint consumption, compared to other embossed panels. The rough surface on the back of ARTZ Embossed Panels ensures that bonding is better when glue is applied and fixed on any substrate.
- 7. ARTZ' embossed panels have a depth of between 0.6mm to 0.8mm depending on the design. This results in better-defined contours and greater visual appeal.
- 8. Century Prowud ARTZ panels have high water-resistant properties due to the quality of glue used during the manufacturing process. These panels are also termite and fungus resistant.
- 9. These panels contain less volatile organic compounds (VOC) which is good for human-health and also makes them environment friendly.

## **POLISHING STEPS**

- 1. First clean the ARTZ embossed panel with a cotton cloth.
- Do sealer coating twice or more on the clear embossed panel.
- 3. Apply Duco Color (Golden/Silver) after soaking the coats (Powder + Lacquer + Thinner)
- 4. After drying, apply lacquer on Duco Color Coating twice or more as per your requirement.
- 5. Apply a mixture of spirit polish and black powder on the whole panel.
- 6. Clean the spirit polish gently with spirit and a cotton cloth.
- 7. Apply lacquer coating after cleaning the panel.
- 8. After coating is complete, use glossy, matt or semi-glossy finish as per your requirement.

## पॉलिश करने की विधि

- 1 सबसे पहले ARTZ एमबोस्ड पैनल को सूती कपड़े से साफ करें।
- 2 साफ किये हुए एमबोस्ड पैनल पर सीलर की दो बार या उससे अधिक जरूरत के हिसाब से कोटिंग करें।
- 3 (पाउडर + लैकर + थिन्न्र) कोटिंग सूखने के बाद पूरे पैनल पर ड्यूको कलर (गोल्डन/सिल्वर) करें।
- 4 सूखने के बाद ड्यूको कलर पर जरूरत के हिसाब से दो बार या उससे अधिक लैकर से कोटिंग करें।
- 5 स्पिरिट पोलिश और काला पाउडर मिलाकर पूरे पैनल पर लगा दें।
- 6 स्पिरिट पोलिश को स्पिरिट और सूती कपड़े से हल्के हाथ से साफ करें।
- 7 साफ करने के उपरान्त पैनल पर लैकर की कोटिंग करें।
- 8 अन्त में ग्लौसी, मैट, सैमी ग्लौसी फिनिश की आप इच्छानुसार कोटिंग कर सकते हैं।

## **TECHNICAL SPECIFICATIONS**

Core material	High Density Fibre Board (HDF)
Thickness	2.3mm
Panel Size	8ft (2440mm) x 4ft (1220mm)
Available in	Raw Unpolished
Polish Type	DUCO Finish / Dual Tone with Antique Effect / PU Finish
Fixing	Fix as Veneer
Applications	Wall/Ceiling Cladding, Shutter Cladding and Furniture Embellishments



Century Plyboards (India) Limited Engineered Panel Products Division

Sales & Marketing Office: Tower B - 8th Floor, Vatika Mindscape, Sector 27D, Faridabad, Haryana - 121003.
Ph.: 7042399909 | Email: prowud@centuryply.com

